

## Technical Data

### Models 123.053 (280 CE), 123.150 (300 CD)

#### Engine

Chassis type	123.053	123.150
Engine	110.984	617.912
Operation	four-stroke gasoline engine mechanical (CIS) fuel injection with airflow sensor	four-stroke diesel engine with MB prechamber
Number of cylinders	6	5
Arrangement of cylinders	upright in line	
Bore/stroke	mm (inches) 86/78.8 (3.39/3.10)	91/92.4 (3.58/3.64)
Total eff. piston displacement	cm <sup>3</sup> (cu. inches) 2746 (167.6)	3005 (183.4)
Compression ratio	8 : 1	21 : 1
Firing Order	1-5-3-6-2-4	1-2-4-5-3
Maximum engine rpm	6500	5100 (no load)
Engine output	SAE net. bhp/rpm 142/5750 <sup>1</sup> ) 137/5750 <sup>2</sup> )	77/4000
Maximum torque	SAE net. lb-ft/rpm 149/4600 <sup>1</sup> ) 142/4600 <sup>2</sup> )	115/2400
Crankshaft bearings	7	6
Valve arrangement	overhead	
Camshaft arrangement	DOHC	OHC
Oil cooling	None	air-oil cooler
Engine cooling	Water circulation pump, thermostat with by/pass line, finned tube radiator, viscous fan	
Lubrication	Forced oil circulation by gear pump	
Oil filter	Full-flow filter	Combination full-flow and by-pass filter
Air filter	Air filter with paper cartridge	

<sup>1)</sup> Federal version

<sup>2)</sup> California version

## Technical Data

### Models 123.053 (280 CE), 123.150 (300 CD)

Chassis type	123.053	123.150
Engine	110.984	617.912

#### Dimensions

Length overall			mm (in.)	4763 (187.5)
Width			mm (in.)	1786 (70.3)
Height, ready-to-drive			mm (in.)	1395 (54.9)
Wheel base			mm (in.)	2710 (106.7)
Track	front		mm (in.)	1488 (58.6)
	rear		mm (in.)	1446 (56.9)
Wheel lock	inside	approx. degrees		43°
	outside	approx. degrees		33°
Turning circle — min. diam.			m (ft.)	11.0 (36.1)

#### Weights

Vehicle curb weight	kg (lbs.)	1590 (3505)	1585 (3495)
Gross vehicle weight (GVWR)	kg (lbs.)	2060 (4540)	2060 (4540)
Gross axle weight rating (GAWR) front/rear	kg (lbs.)	1000/1060 (2205/2340)	1010/1050 (2230/2315)

#### Electrical System

Battery	Voltage Capacity	12 V 55 Ah	12 V 88 Ah
Starter	Bosch	GF 12 V 1.5 KW	F 12 V 2.0 KW
Alternator	Bosch	K1 14 V 55 A 20 maximum output 770 W	

## Technical Data

### Models 123.053 (280 CE), 123.150 (300 CD)

Chassis type	123.053	123.150
Engine	110.984	617.912

#### Filling Capacities

Fuel tank/reserve fuel			approx. ltr. approx. US gal. approx. Imp. gal.	80/11.5 21.1/3.0 17.6/2.5	
Engine	Initial filling	Engine oil	approx. ltr. approx. US qts. approx. Imp. qts.	7.0 7.4 6.2	7.5 7.9 6.6
	Oil and filter change	Engine oil	approx. ltr. approx. US qts. approx. Imp. qts.	6.5 6.9 5.7	
	Oil pan up to markings on oil dipstick	Engine oil	max./min. ltr. max./min. US qts. max./min. Imp. qts.	6/4.5 6.3/4.8 5.3/4.0	5/3.5 5.3/3.7 4.4/3.1
	Oil filter	Engine oil	approx. ltr. approx. US qts. approx. Imp. qts.	0.6 0.6 0.5	1.5 1.6 1.3
	Cooling system with heater	Coolant	approx. ltr. approx. US qts. approx. Imp. qts.	10 10.6 8.8	11 11.6 9.7
Water pump				maintenance free	
Brake system	Brake fluid		approx. ltr. approx. US pts. approx. Imp. pts.	0.5 1.1 0.9	
Automatic transmission Initial filling/ fluid change	Automatic transmission fluid (ATF)		approx. ltr. approx. US qts. approx. Imp. qts.	6.6/5.3 7.0/5.6 5.8/4.7	6.1/4.8 6.4/5.1 5.4/4.2
Rear axle	Hypoid oil SAE 90		approx. ltr. approx. US pts. approx. Imp. pts.	1 2.1 1.8	
Power steering	Automatic transmission fluid (ATF)		approx. ltr. approx. US pts. approx. Imp. pts.	1.4 3 2.5	

## Technical Data

### Models 123.053 (280 CE), 123.150 (300 CD)

Chassis type	123.053	123.105
Engine	110.984	617.912

#### Performance Data

Rear axle ratio			3.54	3.46
Maximum speed in individual gears	1st gear	km/h (mph)	42 (26)	36 (23)
	2nd gear	km/h (mph)	88 (55)	64 (40)
	3rd gear	km/h (mph)	145 (90)	104 (65)
	4th gear	approx. km/h (mph)	180 (112)	143 (89)
Gradability	1st gear slip limit	% (1 in)	41 (2.44)	41 (2.44)
	2nd gear	% (1 in)	41 (2.44)	37 (2.70)
	3rd gear	% (1 in)	23 (4.35)	15 (6.67)
	4th gear	% (1 in)	9 (11.11)	7.5 (13.33)
Acceleration through gears 0 to 100 km/h (0 to 62 mph) Load: 2 persons			12.9 <sup>2)</sup> 13.5 <sup>3)</sup>	20.8
Engine rpm at 100 km/h (62 mph) in high gear			3155	3090

#### Fuel/oil consumption and operating conditions

Fuel consumption during average cross-country driving	ltr./100 km miles per US gal. Imp. gal.	12–19.5 20–12 24–14	9–14 26–17 31–20
Fuel consumption at 110 km/h (68 mph)	ltr./100 km miles per US gal. Imp. gal.	14.8 <sup>2)</sup> 15.4 <sup>3)</sup> 16 <sup>2)</sup> 15 <sup>3)</sup> 19 <sup>2)</sup> 18 <sup>3)</sup>	11.5 20 25
Engine oil consumption (max.)	ltr./100 km miles per US qts. Imp. qts.	0.25 235 282	
Coolant temperature	in working range of thermostat approx. °C (°F) max. temp.	85–100 185–212 approx. °C (°F)	80– 95 176–203
Fuel types		Gasoline, lead-free	Diesel fuel according to ASTM D 975 No. 1–D, 2–D
Anti-knock property	minimum-ROZ	91	---
	minimum-MOZ	81	---

<sup>1)</sup> The  $\pm 7\%$  factor includes possible deviations from permissible engine performance and tire tolerance limits.  
<sup>2)</sup> Federal version.  
<sup>3)</sup> California version.